(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization**

International Bureau



(43) International Publication Date 29 July 2004 (29.07.2004)

PCT

(10) International Publication Number WO 2004/064344 A1

(51) International Patent Classification7: 27/26

H04L 25/02,

(21) International Application Number:

PCT/EP2003/050767

- (22) International Filing Date: 30 October 2003 (30.10.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 02292730.5

31 October 2002 (31.10.2002) EP


- (71) Applicant (for all designated States except US): MO-TOROLA INC [US/US]; 1303 E. Algonquin Road. Schaumburg, IL 60196 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MUCK, Markus [FR/FR]; 67-69, rue de la Colonie, F-75013 Paris (FR). DE COURVILLE, Marc [FR/FR]; 43, rue du Moulin Vert. F-75014 Paris (FR). DEBBAH, Merouane [FR/FR]; 72, rue Camille Desmoulins, F-94230 Cachan (FR).

- (74) Agent: LITCHFIELD, Laura; Motorola, European Intellectual PropertyOperations, Midpoint, Alencon Link, Basingstoke Hampshire RG21 7PL (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD. GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



the OFDM symbol number, modulated as OFDM symbols to be transmitted from a transmitter. Prefixes are inserted as guard intervals in the sample streams and the OFDM symbols are transmitted from the transmitter to a receiver. The receiver uses information from the prefixes to estimate the Channel Impulse Response $(H^{(F)}_D)$ of the transmission channels and uses the estimated Channel Impulse Response $(\hat{H}^{(F)}_D)$ to demodulate the bit streams in the signals received. The prefixes $(\alpha_k.c_o$ to $\alpha_k.c_{D-1})$ are deterministic and are known to the receiver as well as to the transmitter. Preferably, the prefixes $(\alpha_k \cdot c_o)$ to $\alpha_k \cdot c_{D-1}$ comprise a vector (P_D) that is common to said symbols multiplied by at least one weighting factor (α_k) . The weighting factor (α_k) preferably differs from one symbol to another but the elements of a given vector (P_D) are multiplied by the same weighting factor. Preferably, the weighting factor (α_k) has a complex pseudo-random value.

